



Aglime of Australia

PO Box 212, Belmont, WA 6984
Tel : (08) 9277 5529 Fax : (08) 9277 5379

Loading : Kim Riley
0408 092 022



LIME WA INC.

Code of Practice
Accredited
Lime Suppliers



Product Information Sheet

Tested by an Approved Laboratory



NO

YES



GENERAL INFORMATION

Pit Name	<i>Aglime of Australia</i>	Date of Analysis	<i>February 13th 2014</i>
Location	<i>Lancelin</i>	Laboratory No.	<i>B1401-0094-248</i>
Product Description	<i>Limesand</i>	Product Screened	<i>No</i>
Weigh System	<i>Loadrite Loader Scales</i>	Screen Size (mm)	<i>N/A</i>

CODE OF PRACTICE APPROVED LABORATORY REPORT

	THIS SAMPLE	RANGE FOR PIT	THIS SAMPLE	RANGE FOR PIT
Sieve Range (mm)	% Weight		% Neutralising Value	
0.000 - 0.125	4.9	1.7 - 5.0	91.6	90.4 - 92.0
0.125 - 0.250	53.5	35.5 - 60.4	90.6	87.5 - 92.9
0.250 - 0.500	36.3	31.5 - 56.5	94.9	93.7 - 96.2
0.500 - 1.000	5.1	1.9 - 9.7	71.9	66.4 - 95.1
> 1.000	0.1	0.1 - 0.3	Insufficient Sample	86.8
Weighted Average NV			91.2	87.6 - 93.0
Bulk NV	91.6	87.8 - 92.2	<i>Proud to be independently audited by the Department of Agriculture and Food Western Australia.</i>	
Calcium (Ca) (1 M HCl)	33.9	32.6 - 34.1		
Magnesium (Mg) (1 M HCl)	1.7	1.6 - 1.7		
Sodium (Na) (1 M HCl)	0.2	0.1 - 0.3		

Statement by Supplier : The above analysis, provided by a Code of Practice approved laboratory, is a true representation of the product being supplied from the nominated pit. Pit ranges have been calculated from the last 6 samples analysed.

Date : Name : Signature :

Disclaimer : Lime WA Inc. requires members to provide the above details in accordance with the industry Code of Practice requirements but makes no claims and provides no guarantees on the quality or suitability of the product supplied. Product supplied by Lime WA Inc. members occurs naturally and has a moisture retention capacity that varies according to seasonal conditions. As this cannot be controlled by suppliers, moisture level analyses are not included on this information sheet. Lime WA Inc. is not responsible for any claims and/or liabilities arising from the supply and/or use of the product supplied. However, users are invited to contact the Association on 0419 575 737 in the event of any dissatisfaction with the product description provided by accredited lime suppliers.